

WHEELS

Product group	Wheels
Item number	10003424
Valid wheel size	16 X 6.50 - 8
Brand	Deli
Tread pattern	S-368
LI / SI / PR	78 N, 8 PR
TL/TT	TL
Hub design	End cap assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	73
Hub length [mm]	64
Load capacity complete wheel [kg]	330
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 19110134
LI / SI / PR	78 N, 8 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-368
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Maximum air pressure [bar].	6,20

Section width (mm)	170
Stat. radius (SLR) [mm]	192
Rolling circumference [mm].	1290
Tread depth (mm)	5,2
Assembly Item no. Rim	• 10002532
Valid rim size	5.50 A x 8 H2
Load capacity of rim 1 [kg]	330
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
Surface treatment	coated
Rim colour (manufacturer's designation)	John Deere - yellow
RAL	RAL1007
Number of drain holes	3
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0