

WHEELS

Product group	Wheels
Item number	10003436
Valid wheel size	27 x 10 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	5/66.5/112
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	690
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15710547
LI / SI / PR	95 A8 / 107 A8, 8 PR
Load capacity 1 [kg]	690
Speed 1 [km/h].	40
Load capacity 2 [kg]	975
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	35,49
ECE regulation number	ECE 106

Section width (mm)	260
Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2071
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 10002617
Load capacity of rim 1 [kg]	2700
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Disc thickness [mm]	8
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade