

RIMS

Product group	Rims
Item number	10003454
Valid rim size	AG 24.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Offset (mm)	-50
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	9200
Speed Rims 1 [km/h]	40
Axle position agriculture 1	Free Rolling
Load capacity of rim 2 [kg]	6800
Speed Rims 2 [km/h]	65
Axle position agriculture 2	Free Rolling
Load capacity of rim 3 [kg]	10700
Speed Rims 3 [km/h]	25
Axle position agriculture 3	Free Rolling
Load capacity of rim 4 [kg]	4850
Speed of wheels 4 [km/h].	65

Axle position agriculture 4	Drive Wheel
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	79,00
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No