

WHEELS

Product group	Wheels
Item number	10003455
Valid wheel size	270 / 95 R 36
Brand	BKT
Tread pattern	Agrimax RT 955
Valid rim size	W 8 x 36
Rim connection	12/517/600
Bolt hole design	B2
Offset (mm)	-35
Rim colour	Silver
Load capacity complete wheel [kg]	2430
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15727465
LI / SI / PR	139 A8 / 139 B
Load capacity 1 [kg]	2430
Speed 1 [km/h].	40
Load capacity 2 [kg]	2430
Speed 2 [km/h].	50
Direction	Right
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	145,55
ECE regulation number	ECE 106
Section width (mm)	275
Stat. radius (SLR) [mm]	665
Rolling circumference [mm].	4368
Tread depth (mm)	35,0
Number of lugs	25x2
E-Ready	No
Assembly Item no. Rim	• 39123078
Load capacity of rim 1 [kg]	2500
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Number of bolt holes	12
hub hole diameter [mm].	517
Bolt hole circle diameter [mm]	600
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No

Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade