

TYRES

Product group	Tyres
Item number	10003471
Valid tyre size	320 / 55 - 15
LI / SI / PR	121 A8 / 133 A8
TL/TT	TT
Brand	BKT
Tread pattern	TR 678



Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

Technical Informations

Item number	10003471
EAN	8903094076161
Valid tyre size	320 / 55 - 15
LI / SI / PR	121 A8 / 133 A8
TL/TT	TT
Brand	BKT
Tread pattern	TR 678
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,80
Recommended rim size	10LB
Maximum air pressure [bar].	4,00
Section width (mm)	315
Outer diameter of tyre [mm].	735
Tread depth (mm)	18,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A8	1450	40	Drive Wheel	4,00	
133 A8	2060	40	Free Rolling	4,00	