

TYRES

Product group	Tyres
Item number	10003473
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3+





Notes and features

- The Continental Hybrid HT3+ is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- It is suitable for all weather conditions, including winter road conditions.
- Its tread pattern with 4 circumferential grooves and improved pocket sipes guarantees perfect grip.
- The special rubber compound ensures low heat generation and lower fuel consumption.



Technical Informations

Item number	10003473
EAN	4019238071276
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3+
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	В
Wet grip	С
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,00
Recommended rim size	14.00
Maximum air pressure [bar].	9,00
Section width (mm)	426
Outer diameter of tyre [mm].	922
Stat. radius (SLR) [mm]	426
Rolling circumference [mm].	4846
Tread depth (mm)	12,8
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100	Single	9,00	
				9,00	