

TYRES

Product group	Tyres	
Item number	10003481	
Valid tyre size	VF 580 / 80 R 34 CFO 178 D	
LI / SI / PR		
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 372 +	



Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



Technical Informations

Item number	10003481
EAN	8903635053255
Valid tyre size	VF 580 / 80 R 34 CFO
LI / SI / PR	178 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372 +
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	216,50
Recommended rim size	DW20B
Permitted rim size	W18, DW21B
Maximum air pressure [bar].	2,80
Section width (mm)	586
Outer diameter of tyre [mm].	1792
Stat. radius (SLR) [mm]	787
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5269
Contact area [cm²]	3017.1
Tread depth (mm)	57,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	542.18
Guarantee period	10 years

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





E-Ready No	
------------	--

Load capacity

1	ndex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
1	.78 D	7500	65		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.