## Bohnenkamp Moving Professionals

22.09.2024

## RIMS

Product group	Rims
Item number	10003488
Valid rim size	W 12 x 54
Rim connection	12/351/400
Bolt hole design	B3
Offset (mm)	+35
Rim colour	Silver
Brand	TEJWHEELS

## **Technical Informations**

Load capacity of rim 1 [kg]	8200
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	153,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

Disc thickness [mm]	15
Forest reinforcement	flange reinforcement Ø20 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	351
Bolt hole circle diameter [mm]	400
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.