

TYRES

Product group	Tyres
Item number	10003500
Valid tyre size	420 / 80 R 50
LI / SI / PR	165 A8 / 165 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	10003500
EAN	8903094075508
Valid tyre size	420 / 80 R 50
Alternative size 1	16.9R50
LI / SI / PR	165 A8 / 165 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	182,50
Recommended rim size	W13
Permitted rim size	W12
Maximum air pressure [bar].	4,40
Section width (mm)	418
Outer diameter of tyre [mm].	1951
Stat. radius (SLR) [mm]	915
Rolling circumference [mm].	5955
Tread depth (mm)	20,0
Number of lugs	27x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		4,40	
165 B	5150	50		4,40	