

TYRES

Product group	Tyres
Item number	10003507
Valid tyre size	270 / 95 R 54
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	10003507
EAN	8903635031390
Valid tyre size	270 / 95 R 54
Alternative size 1	11.2 R 54
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	103,20
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	5,60
Section width (mm)	285
Outer diameter of tyre [mm].	1900
Stat. radius (SLR) [mm]	901.7
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5862
Contact area [cm ²]	952.6
Tread depth (mm)	36,5
Number of lugs	33x2
Tyre capacity 75% [ltr.]	163.50
Guarantee period	10 years

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		5,60	
156 D	4000	65		5,60	