

## **TYRES**

| Product group         | Tyres           |
|-----------------------|-----------------|
| Item number           | 10003541        |
| Valid tyre size       | 560 / 60 R 22.5 |
| LI / SI / PR          | 169 D           |
| TL/TT                 | TL              |
| Brand                 | Alliance        |
| Tread pattern         | 590             |
| Sonderpostenkategorie | Remaining stock |





## Notes and features

- The Alliance 590 is a flotation radial tyre for use in agriculture and on construction sites.
- Its robust steel belt construction (Steel Belted) and the cut and tear resistant rubber compound enable high load capacities.
- The tyre is ideal for use in the field as well as for on- and off-road applications.



## **Technical Informations**

| Item number                  | 10003541        |
|------------------------------|-----------------|
| EAN                          | 4040658127830   |
| Valid tyre size              | 560 / 60 R 22.5 |
| LI / SI / PR                 | 169 D           |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | 590             |
| Carcass properties           | Steel Belted    |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| Nettogewicht [kg] (gültig)   | 134,00          |
| Recommended rim size         | AG16.00         |
| Maximum air pressure [bar].  | 6,00            |
| Section width (mm)           | 550             |
| Outer diameter of tyre [mm]. | 1244            |
| Stat. radius (SLR) [mm]      | 563             |
| Speed Radius Index (SRI)     | 600             |
| Rolling circumference [mm].  | 3775            |
| Contact area [cm²]           | 1560            |
| Tread depth (mm)             | 23,0            |
| Number of lugs               | 30x2            |
| Tyre capacity 75% [ltr.]     | 269.77          |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 D | 5800               | 65           |               | 6,00                        |              |