

TYRES

Product group	Tyres
Item number	10003541
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	590
Sonderpostenkategorie	Remaining stock



Notes and features

- The Alliance 590 is a flotation radial tyre for use in agriculture and on construction sites.
- Its robust steel belt construction (Steel Belted) and the cut and tear resistant rubber compound enable high load capacities.
- The tyre is ideal for use in the field as well as for on- and off-road applications.

Technical Informations

Item number	10003541
EAN	4040658127830
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	590
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	134,00
Recommended rim size	AG16.00
Maximum air pressure [bar].	6,00
Section width (mm)	550
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	562.80
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3775
Contact area [cm ²]	1560
Tread depth (mm)	23,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	269.77
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		6,00	