

TYRES

Product group	Tyres
Item number	10003544
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Sonderpostenkategorie	Disassambled
type of damage	Dismounted



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10003544
EAN	4040658127861
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	166,68
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	617
Outer diameter of tyre [mm].	1498
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4518
Tread depth (mm)	51,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	405
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	
151 E	3450	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.