

WHEELS

Product group	Wheels
Item number	10003578
Valid wheel size	41 x 18LL - 16.1
Brand	Galaxy
Tread pattern	Turf Special
Valid rim size	W 16.00 C x 16.1
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Anthrazit
Load capacity complete wheel [kg]	2430
Speed complete wheel [km/h]	15



Bohnenkamp
Moving Professionals

GALAXY

Technical Informations

Assembly Item no. Tyres	• 12011500
LI / SI / PR	139 A3 / 135 A6, 6 PR
Load capacity 1 [kg]	2430
Speed 1 [km/h].	15
Load capacity 2 [kg]	2240
Speed 2 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	73,85
ECE regulation number	ECE 106
Section width (mm)	487

Stat. radius (SLR) [mm]	466
Rolling circumference [mm].	3003
E-Ready	No
Assembly Item no. Rim	• 10003147
Load capacity of rim 1 [kg]	2450
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	30
Maximum air pressure [bar].	1,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade