

WHEELS

Product group	Wheels
Item number	10003580
Valid wheel size	235 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	120



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066122
LI / SI / PR	143 / 141 L, 16 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	120
Load capacity 3 [kg]	2575
Speed 3 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	55,53
ECE regulation number	ECE 54 ECE 117
Section width (mm)	235
Stat. radius (SLR) [mm]	372.06
Rolling circumference [mm].	2343
Tread depth (mm)	13,0
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060060
Load capacity of rim 1 [kg]	4050
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	120
Maximum air pressure [bar].	8,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC

Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade