

## WHEELS

Product group	Wheels
Item number	10003581
Valid wheel size	145 / 80 R 10
Brand	Kenda
Tread pattern	KR209 KargoTrail 3G
Valid rim size	3.50 B x 10 H2
Rim connection	4/60/100
Rim colour	Silver
Load capacity complete wheel [kg]	375
Speed complete wheel [km/h]	140



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19266064
LI / SI / PR	74 N
Load capacity 1 [kg]	375
Speed 1 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	7,83
ECE regulation number	ECE 30
Section width (mm)	144
Stat. radius (SLR) [mm]	217

Rolling circumference [mm].	1479
Tread depth (mm)	5,0
E-Ready	No
Assembly Item no. Rim	• 39600289
Load capacity of rim 1 [kg]	500
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	3,40
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	14.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

---

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade