

TYRES

Product group	Tyres
Item number	10003585
Valid tyre size	875 / 65 R 29
LI / SI / PR	221 A2 / 203 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41



Notes and features

- The improved tread design provides maximum traction.
- All steel carcass with reinforced steel belt ply provides excellent stability and puncture resistance.
- The special tread compound (C.R. = Cut Resistance) offers best cut resistance in combination with excellent mileage and wear properties.
- Especially suitable for use on wheel loaders and dumpers.
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	10003585
EAN	8903094064359
Valid tyre size	875 / 65 R 29
Alternative size 1	35/65R29
LI / SI / PR	221 A2 / 203 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41
TRA Code	L4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	774,00
Recommended rim size	27.00/3.5
Permitted rim size	27.00/3.0, 28.00/3.5
Maximum air pressure [bar].	6,25
Section width (mm)	880
Outer diameter of tyre [mm].	1865
Stat. radius (SLR) [mm]	837
Rolling circumference [mm].	5680
Tread depth (mm)	60,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
221 A2	25750	10	Loader dozer	6,25	
203 B	15500	50	Transport	4,75	