

## TYRES

Product group	Tyres
Item number	10003589
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	146 A8 / 158 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Flotation tyre for high payloads with low inflation pressure
- Minimal soil compaction
- Suitable for road and field use

## Technical Informations

Item number	10003589
EAN	8903094058518
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	146 A8 / 158 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	62,36
Recommended rim size	AG16.00
Maximum air pressure [bar].	4,50
Section width (mm)	500
Outer diameter of tyre [mm].	3167
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	1045
Tread depth (mm)	18,5
Number of lugs	26x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40	Drive Wheel	4,50	LLV
158 A8	4250	40	Free Rolling	4,50	LLV