

## WHEELS

Product group	Wheels
Item number	10003590
Valid wheel size	280 / 80 R 18
Brand	BKT
Tread pattern	Multimax MP 522
Valid rim size	9 x 18
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2000
Speed complete wheel [km/h]	50
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15735216
LI / SI / PR	132 A8 / 132 B
Load capacity 1 [kg]	2000
Speed 1 [km/h].	40
Load capacity 2 [kg]	2000
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	66,57
ECE regulation number	ECE 106

Section width (mm)	282
Stat. radius (SLR) [mm]	421
Rolling circumference [mm].	2748
Tread depth (mm)	33,5
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 32010135
Load capacity of rim 1 [kg]	3350
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1800
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

---

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade