

WHEELS

Product group	Wheels
Item number	10003612
Valid wheel size	23 x 10.50 - 12
Brand	BKT
Tread pattern	TR 315
Valid rim size	7.00 I x 12
Rim connection	5/94/140
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	850
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15710494
LI / SI / PR	106 A3 /102 A6, 8 PR
Load capacity 1 [kg]	950
Speed 1 [km/h].	15
Load capacity 2 [kg]	850
Speed 2 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,14
ECE regulation number	ECE 106

Section width (mm)	255
Stat. radius (SLR) [mm]	260
Rolling circumference [mm].	1840
Tread depth (mm)	15,5
E-Ready	No
Assembly Item no. Rim	• 30820110
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	30
Maximum air pressure [bar].	3,00
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Bolt hole diameter [mm]	18.5
Spherical countersink [mm].	R14
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of drain holes	1
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade