

TYRES

Product group	Tyres	
Item number	10003613	
Valid tyre size	800 / 40 - 26.5	
LI / SI / PR	183 A2/176A2, 24 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 644 III	





Technical Informations

Item number	10003613
EAN	8903635047780
Valid tyre size	800 / 40 - 26.5
LI / SI / PR	183 A2/176A2, 24 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 644 III
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	270,80
Recommended rim size	AG28.00
Maximum air pressure [bar].	6,00
Section width (mm)	790
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	622
Speed Radius Index (SRI)	625
Rolling circumference [mm].	4105
Contact area [cm²]	1958.9
Tread depth (mm)	51,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	352.73
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A2	8750	10		6,00	
176 A8	7100	40		6,00	_

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.