

TYRES

Product group	Tyres
Item number	10003614
Valid tyre size	15.5 / 55 R 18
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Alliance
Tread pattern	601



Notes and features

- For small wheel loaders and excavators with M+S marking.
- Radial tyre with strong nylon construction and steel belt.
- High contact area ensures good pressure distribution.

Technical Informations

Item number	10003614
EAN	8903635021773
Valid tyre size	15.5 / 55 R 18
Alternative size 1	385/55R18
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Alliance
Tread pattern	601
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,40
Recommended rim size	11
Maximum air pressure [bar].	3,50
Section width (mm)	370
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	395
Speed Radius Index (SRI)	425
Rolling circumference [mm].	2686
Contact area [cm ²]	697.5
Tread depth (mm)	17,6
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		3,50	
140 B	2500	50		3,50	