

TYRES

Product group	Tyres
Item number	10003670
Valid tyre size	460 / 70 R 24
LI / SI / PR	165 A2 / 154 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.

Technical Informations

Item number	10003670
EAN	8903635022688
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5L24
LI / SI / PR	165 A2 / 154 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	102,70
Recommended rim size	W15
Maximum air pressure [bar].	4,00
Section width (mm)	455
Outer diameter of tyre [mm].	1254
Stat. radius (SLR) [mm]	557.3
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3635
Contact area [cm ²]	1222.1
Tread depth (mm)	27,8
Number of lugs	23x2
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A2	5150	10		4,00	
154 B	3750	50		4,00	