

TYRES

Product group	Tyres
Item number	10003677
Valid tyre size	300 / 70 R 16.5
LI / SI / PR	137 A8 / 137 B
TL/TT	TL
Brand	BKT
Tread pattern	Skidmax SR-Skidder



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Skidmax SR-Skidder is a radial tyre for skid loaders, backhoe loaders and telehandlers.
- It is ideal for use on hard surfaces, such as road construction or landfills.
- Due to its all-steel carcass, the tyre is particularly low-wear, durable and allows high load capacities.
- Its tread pattern with the circumferential rib in the tread center and the extremely low-wear and antistatic rubber compound ensure good traction and a long service life.
- The extra thick sidewall and rim guard protect the tyre from damage.

Technical Informations

Item number	10003677
EAN	8903094069439
Valid tyre size	300 / 70 R 16.5
Alternative size 1	12R16.5
LI / SI / PR	137 A8 / 137 B
TL/TT	TL
Brand	BKT
Tread pattern	Skidmax SR-Skidder
Antistatic	No
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	44,50
Recommended rim size	9.75
Maximum air pressure [bar].	5,00
Section width (mm)	306
Outer diameter of tyre [mm].	830
Stat. radius (SLR) [mm]	378
Rolling circumference [mm].	2530
Tread depth (mm)	21,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A8	2300	40		5,00	
137 B	2300	50		5,00	