

TYRES

Product group	Tyres	
Item number	10003735	
Valid tyre size	710 / 70 R 42	
LI / SI / PR	173 D / 170 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Stud damage	



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10003735
EAN	4040658129773
Valid tyre size	710 / 70 R 42
LI / SI / PR	173 D / 170 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	332,40
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	732
Outer diameter of tyre [mm].	2096
Stat. radius (SLR) [mm]	942
Rolling circumference [mm].	6288
Tread depth (mm)	58,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	831.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,40	
170 E	6000	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.