

TYRES

Product group	Tyres
Item number	10003738
Valid tyre size	600 / 65 R 28
LI / SI / PR	157 A8 / 154 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Sonderpostenkategorie	Damaged
type of damage	Dismounted, Flap damage



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp
- Its big contact area provides excellent traction
- The flexible sidewalls enable high load capacities even at low inflation pressure

Technical Informations

Item number	10003738
EAN	4040658129803
Valid tyre size	600 / 65 R 28
LI / SI / PR	157 A8 / 154 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,10
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	606
Outer diameter of tyre [mm].	1494
Stat. radius (SLR) [mm]	664
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4444
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		2,40	
154 D	3750	65		2,40	