

TYRES

Product group	Tyres
Item number	10003743
Valid tyre size	540 / 65 R 24
LI / SI / PR	146 D / 143 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Sonderpostenkategorie	Damaged
type of damage	Dismounted



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10003743
EAN	4040658129841
Valid tyre size	540 / 65 R 24
LI / SI / PR	146 D / 143 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	127,80
Recommended rim size	DW16L
Permitted rim size	W16L, DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	525
Outer diameter of tyre [mm].	1308
Stat. radius (SLR) [mm]	579
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3920
Tread depth (mm)	50,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	261
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 D	3000	65		2,40	
143 E	2725	70		2,40	