

TYRES

Product group	Tyres	
Item number	10003749	
Valid tyre size	650 / 65 R 42	
LI / SI / PR	165 D / 161 E	
TL/TT	TL	
Brand	Bridgestone	
Tread pattern	VX-Tractor	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted	





Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.



Technical Informations

Item number	10003749
EAN	4040658129902
Valid tyre size	650 / 65 R 42
LI / SI / PR	165 D / 161 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	286,23
Recommended rim size	DW20B
Section width (mm)	646
Outer diameter of tyre [mm].	1911
Stat. radius (SLR) [mm]	876
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5753
Tread depth (mm)	60,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	592
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65			
161 E	4625	70			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.