

## **RIMS**

Product group	Rims
Item number	10003817
Valid rim size	6.00 J x 16 H2
Rim connection	6/161.5/205
Bolt hole design	A2
Offset (mm)	-12
Rim colour	Silver
Brand	Jantsa



## **Technical Informations** Load capacity of rim 1 [kg] 1650 Speed Rims 1 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Towed axle Nettogewicht [kg] (gültig) 14,00 H2 Hump Single / multi-part einteilig Rim material steel RAL RAL9006 **Cavity Sealed** No 8 Disc thickness [mm]

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161.5
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No