

TYRES

Product group	Tyres
Item number	10003833
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp
■ ■ ● Moving Professionals

DEESTONE

Notes and features

- The Deestone SV401 is an all-position truck tyre for regional transport.
- Its 5-rib tread pattern with wide tyre shoulder provides excellent driving stability and safe handling, particularly on steering and trailer axles.
- 4 wide grooves guarantee efficient water drainage resulting in very good braking performance in wet and dry road conditions.
- The special rubber compound enables low heat generation and a long service life.

Technical Informations

Item number	10003833
EAN	4040658130885
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	29,00
Recommended rim size	6.75
Maximum air pressure [bar].	8,75
Section width (mm)	233
Outer diameter of tyre [mm].	797
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 L	2180	120	Single	8,75	
133 L	2060	120	Twin	8,75	