Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	10003834
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	140 / 138 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
Sonderpostenkategorie	DOT
type of damage	DOT





Notes and features

- The Deestone SV401 is an all-position truck tyre for regional transport.
- Its 5-rib tread pattern with wide tyre shoulder provides excellent driving stability and safe handling, particularly on steering and trailer axles.
- 4 wide grooves guarantee efficient water drainage resulting in very good braking performance in wet and dry road conditions.
- The special rubber compound enables low heat generation and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10003834
EAN	4040658130892
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	140 / 138 L, 16 PR
	1407 130 L, 10 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	63,00
Recommended rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	262
Outer diameter of tyre [mm].	873
Tread depth (mm)	14,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 L	2500	120	Single	8,30	
138 L	2360	120	Twin	8,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.