# Bohnenkamp Moving Professionals

15.11.2024

### **TYRES**

Product group	Tyres
Item number	10003835
Valid tyre size	12.00 R 20
LI / SI / PR	154 / 151 K, 18 PR
TL/TT	тт
SET	Tube
Brand	Deestone
Tread pattern	SK423
Sonderpostenkategorie	DOT
type of damage	DOT



#### **Technical Informations**

Item number	10003835
EAN	4040658130908
Valid tyre size	12.00 R 20
LI / SI / PR	154 / 151 K, 18 PR
TL/TT	ТТ
SET	Tube
Brand	Deestone
Tread pattern	SK423
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	C

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	76,98
Recommended rim size	8.50
Maximum air pressure [bar].	8,30
Section width (mm)	305
Outer diameter of tyre [mm].	1118
Tread depth (mm)	17,3
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 K	3750	110	Single	8,30	
151 K	3450	110	Twin	8,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.