

TYRES

Product group	Tyres
Item number	10003836
Valid tyre size	11 R 24.5
LI / SI / PR	149 / 146 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SK421
Sonderpostenkategorie	DOT
type of damage	DOT





Notes and features

- The Deestone SK421 is a truck tyre for all axles for mixed
 use
- Its tread pattern design with a combination of ribs and blocks provides very high traction and slow wearing.
- Zigzag-shaped grooves provide good grip on wet, dry and snowy road roads.
- Thanks to its abrasion-resistant rubber compound, the tyre is excellently suited to on- and off-road use and protected from cut and tear damages.



Technical Informations

Item number	10003836
EAN	4040658130915
Valid tyre size	11 R 24.5
LI / SI / PR	149 / 146 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SK421
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	С
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	65,50
Recommended rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	279
Outer diameter of tyre [mm].	1104
Tread depth (mm)	17,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 L	3250	120	Single	8,30	
146 L	3000	120	Twin	8,30	