

## WHEELS

Product group	Wheels
Item number	10003837
Valid wheel size	205 / 65 R 17.5
Brand	Sailun
Tread pattern	Regio Pro STR2 MAX
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-60
Rim colour	Silver
Load capacity complete wheel [kg]	2000
Speed complete wheel [km/h]	100
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 10002059
LI / SI / PR	132 / 130 J (133 / 133 F), 18 PR
Load capacity 1 [kg]	2000
Speed 1 [km/h].	100
Load capacity 2 [kg]	2060
Speed 2 [km/h].	80
Load capacity 3 [kg]	1900
Speed 3 [km/h].	100
Load capacity 4 [kg]	2060

Speed 4 [km/h].	80
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	52,03
ECE regulation number	ECE 54 ECE 117
Section width (mm)	205
Tread depth (mm)	11,5
Rolling resistance	D
Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 10003630
Load capacity of rim 1 [kg]	3700
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade