

RIMS

Product group	Rims
Item number	10003844
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Black
Brand	Moveero

Technical Informations

Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	11900
Speed Rims 3 [km/h]	50
Maximum speed [km/h].	65
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	153,50
Hump	kein Hump
Single / multi-part	einteilig

Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Number of additional holes	1
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No