

TYRES

Product group	Tyres	
Item number	10003872	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	157 / 154 M, 20 PR	
TL/TT	TL	
Brand	Fullrun	
Tread pattern	TB875A	
Sonderpostenkategorie	DOT	
type of damage	DOT	





Notes and features

- The Fullrun TB875A is a truck tyre for all axles on trucks and buses.
- The tread compound is especially wear resistant and guarantees a long service life for the tyre.



Technical Informations

Item number	10003872
EAN	4040658131271
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	157 / 154 M, 20 PR
TL/TT	TL
Brand	Fullrun
Tread pattern	TB875A
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA/TR/FA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	58,73
Recommended rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Tread depth (mm)	17,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 M	4125	130	Single	9,00	
154 M	3750	130	Twin	9,00	