

## TYRES

Product group	Tyres
Item number	10003873
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp  
■ ■ ● Moving Professionals

**DEESTONE**

## Notes and features

- The Deestone SV401 is an all-position truck tyre for regional transport.
- Its 5-rib tread pattern with wide tyre shoulder provides excellent driving stability and safe handling, particularly on steering and trailer axles.
- 4 wide grooves guarantee efficient water drainage resulting in very good braking performance in wet and dry road conditions.
- The special rubber compound enables low heat generation and a long service life.

## Technical Informations

Item number	10003873
EAN	4040658131288
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV401
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA/TR/FA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	72,80
Maximum air pressure [bar].	8,50
Section width (mm)	296
Outer diameter of tyre [mm].	1056
Stat. radius (SLR) [mm]	832
Rolling circumference [mm].	3156
Tread depth (mm)	16,4
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,50	
149 M	3250	130	Twin	8,50	