

TYRES

Product group	Tyres
Item number	10003875
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV403
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp
■ ■ ● Moving Professionals

DEESTONE

Notes and features

- The Deestone SV403 is a truck steering axle tyre for regional transport.
- Its 5-rib tread pattern with wider tyre shoulder provides very good driving stability.
- Four wide, straight grooves guarantee reliable water drainage and good braking performance in wet and dry road conditions.
- Its rubber compound provides low heat generation and long durability.

Technical Informations

Item number	10003875
EAN	4040658131301
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 L, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SV403
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	71
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	66,30
Recommended rim size	9.00
Maximum air pressure [bar].	8,50
Section width (mm)	306
Outer diameter of tyre [mm].	1056
Stat. radius (SLR) [mm]	489
Rolling circumference [mm].	3072
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	8,50	
149 L	3250	120	Twin	8,50	