

WHEELS

Product group	Wheels
Item number	10003906
Valid wheel size	620 / 40 R 22.5
Brand	BKT
Tread pattern	FL 635
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3750
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715138
LI / SI / PR	154 D
Load capacity 1 [kg]	3750
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	162,57
ECE regulation number	ECE 106
Section width (mm)	625
Stat. radius (SLR) [mm]	470

Rolling circumference [mm].	3249
Tread depth (mm)	28,5
E-Ready	No
Assembly Item no. Rim	• 33060409
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade