

TYRES

Product group	Tyres
Item number	10003956
Valid tyre size	VF 270 / 95 R 32
LI / SI / PR	148 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10003956
EAN	8903094076352
Valid tyre size	VF 270 / 95 R 32
LI / SI / PR	148 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,71
Recommended rim size	W9
Permitted rim size	W10
Maximum air pressure [bar].	4,00
Section width (mm)	280
Outer diameter of tyre [mm].	1339
Stat. radius (SLR) [mm]	617
Rolling circumference [mm].	4080
Tread depth (mm)	35,0
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 D	3150	65		4,00	