# Bohnenkamp Moving Professionals

#### **TYRES**

Product group	Tyres
Item number	10004252
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	175 A8 / 175 B
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331





#### Notes and features

- The Alliance 331 is perfectly suited to on- and off-road • agricultural applications e.g. for tractors, agricultural trailers and similar vehicles
- Its main characteristics are a high load capacity and low • inflation pressure
- It replaces conventional tractor tyres or dual constructions . because of its high traction, high load capacity and at the same time protects the soil
- Thanks to the permitted speed of 50 km/h, it can also be • used on off-road trucks and trailers
- The strong nylon construction and special rubber . compound make the tyre very durable

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10004252
EAN	8903635058977
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	175 A8 / 175 B
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	131,60
Recommended rim size	AG20.00
Maximum air pressure [bar].	6,00
Section width (mm)	645
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	537
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3566
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	245.25
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		6,00	
175 B	6900	50		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.