

TYRES

Product group	Tyres	
Item number	10004350	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	168 A8 / 175 A2, 20 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 644 III ELIT	





Technical Informations

Item number	10004350
EAN	8903635047513
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	168 A8 / 175 A2, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 644 III ELIT
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	223,00
Recommended rim size	AG24.00
Maximum air pressure [bar].	2,50
Section width (mm)	690
Outer diameter of tyre [mm].	1345
Stat. radius (SLR) [mm]	608
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3964
Contact area [cm²]	1945.6
Tread depth (mm)	51,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	292.58
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		2,50	
175 A2	6900	10		2,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.