

## TYRES

Product group	Tyres
Item number	10004489
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	Alliance
Tread pattern	590



## Notes and features

- The Alliance 590 is a flotation radial tyre for use in agriculture and on construction sites.
- Its robust steel belt construction (Steel Belted) and the cut and tear resistant rubber compound enable high load capacities.
- The tyre is ideal for use in the field as well as for on- and off-road applications.

**Technical Informations**

Item number	10004489
EAN	8903635057055
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	Alliance
Tread pattern	590
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,90
Recommended rim size	AG20.00
Maximum air pressure [bar].	5,00
Section width (mm)	611
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	529
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3547
Contact area [cm <sup>2</sup> ]	1526.7
Tread depth (mm)	23,0
Tyre capacity 75% [ltr.]	270.3
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		5,00	