Bohnenkamp Moving Professionals

13.03.2025

TYRES

Product group	Tyres	
Item number	10004538	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	154 / 150 M, 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	Transport Pro S	



Technical Informations

Item number	10004538
EAN	8935341215900
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 150 M, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	Transport Pro S
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Carcass properties	EcoPoint3

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rolling resistance	В
Wet grip	A
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	62,72
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	298
Tread width (mm)	248
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	487
Rolling circumference [mm].	3184
Tread depth (mm)	15,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,50	
150 M	3350	130	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.