

## TYRES

|                 |                   |
|-----------------|-------------------|
| Product group   | Tyres             |
| Item number     | 10165125          |
| Valid tyre size | 195 / 65 R 16 C   |
| LI / SI / PR    | 104 / 102 R, 8 PR |
| TL/TT           | TL                |
| Brand           | Onyx              |
| Tread pattern   | NY-W287           |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The Onyx NY-W287 is a winter tyre for vans.
- Its rubber compound ensures low rolling resistance.
- Its block tread pattern with 3 circumferential zigzag grooves and many sipes provides good grip on wet and cold roads as well as on ice and snow.
- Its reinforced casing enables high loading capacities and a long service life.

## Technical Informations

|                              |                   |
|------------------------------|-------------------|
| Item number                  | 10165125          |
| EAN                          | 6953913187822     |
| Valid tyre size              | 195 / 65 R 16 C   |
| LI / SI / PR                 | 104 / 102 R, 8 PR |
| TL/TT                        | TL                |
| Brand                        | Onyx              |
| Tread pattern                | NY-W287           |
| M+S                          | M+S               |
| 3PMSF                        | 3PMSF             |
| Rolling resistance           | D                 |
| Wet grip                     | D                 |
| Rolling noise [db].          | 73                |
| Rolling noise level          | B                 |
| Antistatic                   | No                |
| Tyre colour                  | Black             |
| ECE regulation number        | ECE 54,ECE 117    |
| Nettogewicht [kg] (gültig)   | 11,18             |
| Recommended rim size         | 6J                |
| Permitted rim size           | 5.50J             |
| Maximum air pressure [bar].  | 4,75              |
| Section width (mm)           | 201               |
| Outer diameter of tyre [mm]. | 660               |
| Rolling circumference [mm].  | 2000              |
| Tread depth (mm)             | 9,7               |
| E-Ready                      | No                |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 104 R | 900                | 170          | Single        | 4,75                     |              |
| 102 R | 850                | 170          | Twin          | 4,80                     |              |