

TYRES

| Product group | Tyres | |
|-----------------|-------------------|--|
| Item number | 10165235 | |
| Valid tyre size | 205 / 65 R 16 C | |
| LI / SI / PR | 107 / 105 T, 8 PR | |
| TL/TT | TL | |
| Brand | Onyx | |
| Tread pattern | NY-AS 687 | |



Notes and features

- The Onyx NY-AS 687 is an all-season tyre for vans.
- Its tread pattern provides a very good performance on dry, wet and snow-covered roads.
- Three circumferential, jagged grooves prevent aquaplaning and ensure driving safety in difficult weather conditions.
- Small sipes on the tread ribs improve adhesion in rain and snow
- The high-grip silica compound guarantees good driving performance and low rolling resistance.



Technical Informations

| Item number | 10165235 |
|------------------------------|-------------------|
| EAN | 6953913188423 |
| Valid tyre size | 205 / 65 R 16 C |
| LI / SI / PR | 107 / 105 T, 8 PR |
| TL/TT | TL |
| Brand | Onyx |
| Tread pattern | NY-AS 687 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Rolling resistance | D |
| Wet grip | D |
| Rolling noise [db]. | 73 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 12,30 |
| Recommended rim size | 6J |
| Permitted rim size | 5.50J, 6.50J |
| Maximum air pressure [bar]. | 4,75 |
| Section width (mm) | 209 |
| Outer diameter of tyre [mm]. | 672 |
| Tread depth (mm) | 9,7 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 107 T | 975 | 190 | Single | 4,75 | |
| 105 T | 925 | 190 | Twin | 4,80 | |