

TYRES

Product group	Tyres
Item number	10165340
Valid tyre size	175 R 13 C
LI / SI / PR	97 / 95 R, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-06



Notes and features

- The Onyx NY-06 is a summer tyre for light trucks and transporters.
- Its zigzag circumferential grooves with horizontal sipes guarantee very good grip on wet and dry roads.
- The reinforced casing with 2 steel belts protects against damages and enables high loading capacities.
- Its particularly wear-resistant rubber compound provides low heat generation and a long service life.
- The variable pitch design guarantees ride comfort and low noise emission.

Technical Informations

Item number	10165340
EAN	6953913186399
Valid tyre size	175 R 13 C
LI / SI / PR	97 / 95 R, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-06
M+S	M+S
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	8,46
Recommended rim size	5.00B
Permitted rim size	4.50J, 5.50J
Maximum air pressure [bar].	4,50
Section width (mm)	178
Outer diameter of tyre [mm].	610
Stat. radius (SLR) [mm]	277
Rolling circumference [mm].	1848
Tread depth (mm)	7,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
97 R	730	170	Single	4,50	
95 R	690	170	Twin	4,50	