

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 10165420 |
| Valid tyre size | 205 / 65 R 16 C |
| LI / SI / PR | 107 / 105 T, 8 PR |
| TL/TT | TL |
| Brand | Onyx |
| Tread pattern | NY-06 |



Notes and features

- The Onyx NY-06 is a summer tyre for light trucks and transporters.
- Its zigzag circumferential grooves with horizontal sipes guarantee very good grip on wet and dry roads.
- The reinforced casing with 2 steel belts protects against damages and enables high loading capacities.
- Its particularly wear-resistant rubber compound provides low heat generation and a long service life.
- The variable pitch design guarantees ride comfort and low noise emission.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 10165420 |
| EAN | 6953913186467 |
| Valid tyre size | 205 / 65 R 16 C |
| LI / SI / PR | 107 / 105 T, 8 PR |
| TL/TT | TL |
| Brand | Onyx |
| Tread pattern | NY-06 |
| M+S | M+S |
| Rolling resistance | D |
| Wet grip | C |
| Rolling noise [db]. | 72 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 12,50 |
| Recommended rim size | 6J |
| Permitted rim size | 5.50J, 6.50J |
| Maximum air pressure [bar]. | 4,75 |
| Section width (mm) | 209 |
| Outer diameter of tyre [mm]. | 672 |
| Stat. radius (SLR) [mm] | 309 |
| Rolling circumference [mm]. | 2036 |
| Tread depth (mm) | 9,7 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 107 T | 975 | 190 | Single | 4,75 | |
| 105 T | 925 | 190 | Twin | 4,75 | |