

TYRES

Product group	Tyres	
Item number	10165430	
Valid tyre size	215 / 65 R 16 C	
LI / SI / PR	109 /107 T, 8 PR	
TL/TT	TL	
Brand	Onyx	
Tread pattern	NY-06	



Notes and features

- The Onyx NY-06 is a summer tyre for light trucks and transporters.
- Its zigzag circumferential grooves with horizontal sipes guarantee very good grip on wet and dry roads.
- The reinforced casing with 2 steel belts protects against damages and enables high loading capacities.
- Its particularly wear-resistant rubber compound provides low heat generation and a long service life.
- The variable pitch design guarantees ride comfort and low noise emission.



Technical Informations

Item number	10165430
EAN	6953913188584
Valid tyre size	215 / 65 R 16 C
LI / SI / PR	109 /107 T, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-06
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	13,16
Recommended rim size	6.50J
Permitted rim size	6J, 7J
Maximum air pressure [bar].	4,75
Section width (mm)	221
Outer diameter of tyre [mm].	686
Stat. radius (SLR) [mm]	315
Rolling circumference [mm].	2079
Tread depth (mm)	9,7
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 T	1030	190	Single	4,75	
107 T	975	190	Twin	4,75	