

TYRES

Product group	Tyres	
Item number	10165450	
Valid tyre size	235 / 65 R 16 C	
LI / SI / PR	115 / 113 T, 8 PR	
TL/TT	TL	
Brand	Onyx	
Tread pattern	NY-06	



Notes and features

- The Onyx NY-06 is a summer tyre for light trucks and transporters.
- Its zigzag circumferential grooves with horizontal sipes guarantee very good grip on wet and dry roads.
- The reinforced casing with 2 steel belts protects against damages and enables high loading capacities.
- Its particularly wear-resistant rubber compound provides low heat generation and a long service life.
- The variable pitch design guarantees ride comfort and low noise emission.



Technical Informations

Item number	10165450
EAN	6953913186474
Valid tyre size	235 / 65 R 16 C
LI / SI / PR	115 / 113 T, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-06
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	14,79
Recommended rim size	73
Permitted rim size	6.50J, 7.50
Maximum air pressure [bar].	4,75
Section width (mm)	240
Outer diameter of tyre [mm].	712
Stat. radius (SLR) [mm]	325
Rolling circumference [mm].	2157
Tread depth (mm)	9,7
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 T	1215	190	Single	4,75	
113 T	1150	190	Twin	4,80	